




## DIMENSIONS



W	H	X	BASE MODEL NO.
24"	36"	8 1/2"	<b>S2050-L32</b>
24"	36"	8 1/2"	<b>S2050-L48</b>
30"	36"	8 1/2"	<b>S2051-L48</b>
36"	42"	9 1/2"	<b>S2052-L60</b>
42"	48"	11"	<b>S2053-L72</b>

## SPECIFICATIONS

**Driver:** 0-10V dimming to 1%, 120/277

**Mounting:** Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided.

## FEATURES

- Opal Matte Acrylic Bowl
- LED 0-10V Dimming Driver

## ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + Finish Code + Option Code

S2050-L32	+	27K	+	PT	BN	+	OA	+	Option
S2050-L48		30K		CC	PB				
S2051-L48		35K		AP	PC				
S2052-L60		40K		BA					
S2053-L72									

## FINISHES

<b>AP</b> Aged Pewter	<b>PC</b> Polished Chrome
<b>BA</b> Brushed Aluminum	<b>CC</b> Custom Painted Finish
<b>BN</b> Brushed Nickel	<b>PT</b> Powder Coated Finishes*
<b>PB</b> Polished Brass	

\*(Specify Color Code from the list of Powder Coating Finishes)

## OPTIONS

**BAC** Buy America; Buy American Act; and Build America, Buy America Act Compliant.

**EML** Remote 10W Emergency LED Battery Backup (Requires Additional Power Cable)

**SWC** 35-Degree Swivel Canopy

**2C** Two-Circuit Wiring

**3S** Three Stems

**FAA** Faux Alabaster Acrylic (Hand Painted) [FA1 White; FA2 Antique; FA3 Grey; FA4 Taupe; FA5 Honey; FA6 Tuscan]

**1S4AC** Single Stem with (4) Aircraft Cables

## LIGHT OUTPUT

**LXX** = ~ 88 LPW Delivered Lumens (Example: L32= 32W x 88LPW = 2,816 Lumens)