




DIMENSIONS



W	H	X	BASE MODEL NO.
27 1/2"	36"	10"	S2200-L48
33 1/2"	36"	13"	S2201-L60
39 1/2"	36"	13"	S2202-L72
45 1/2"	36"	15 1/2"	S2203-L108

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided.

FEATURES

- Opal Matte Acrylic Bowl
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + Finish Code + OA + Option Code

S2200-L48	+	27K	+	PT	+	OA	+	Option
S2201-L60		30K		BA				
S2202-L72		35K		BB				
S2203-L108		40K		BC				
				PB				
				PC				

FINISHES

BA Brushed Aluminum	PB Polished Brass
BB Brushed Brass	PC Polished Chrome
BC Brushed Chrom	PT Powder Coated Finishes*

*(Specify Color Code from the list of Powder Coating Finishes)

OPTIONS

- BAC** Buy America; Buy American Act; and Build America, Buy America Act Compliant.
- EML** Remote 10W Emergency LED Battery Backup (Requires Additional Power Cable)
- FAA** Faux Alabaster Acrylic (Hand Painted) [FA1 White; FA2 Antique; FA3 Grey; FA4 Taupe; FA5 Honey; FA6 Tuscan]
- SWC** 35-Degree Swivel Canopy
- 2C** Two-Circuit Wiring
- 3S** Three Stems
- 4A** Four Trim Bars

LIGHT OUTPUT

LXX = ~ 81 LPW Delivered Lumens (Example: L48= 48W x 81LPW = 3,888 Lumens)

S2200 Series



Three Stem Option



Four Arms Over Diffuser Option

www.ScottArchLighting.com | Tel (707) 864-2172 | Fax (707) 864-2182
© Copyright 2024 Scott Architectural Lighting. All Rights Reserved. Made in the USA.

