
S2270 Series



DIMENSIONS



W 13″ H 36″ **X** 20″ SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277 Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided.

FEATURES

Opal Matte Acrylic Cylinder

• LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Code	Lamp	Code	+ C(CT + F	inish	+ Fa	bric +	OA -	F Option
S2270-L32	+	27K 30K 35K 40K	+	PT BA BB BC		+	OA	+	Option
FINISHES									
BA Brushed / BB Brushed E BC Brushed (BN Brushed I *(Specify Color OPTIONS	Brass Chrom Nickel	е		PC P PN P PT P		d Chi d Nic Coat	rome kel ted Fir		5 *
BAC Buy Am America Act EML Remote OA Specify C FAA Faux Ala Antique; FA3 SWC 35-Dec	Comp 10W Overal abaste Grey	oliant. Emerg I Heig er Acry ; FA4	genc ht of /lic (Taup	y LED Fixtur Hand e; FA5	Batte e in Ir Painte Hone	ery Ba nche: ed) [l ey, Fa	ackup s; E.G FA1 W A6 Tus	. – O. 'hite; scan]	A48 FA2,
LIGHT OUTP	UT								

LXX = ~ 65 LPW Delivered Lumens (Example: L32= 32W x 65LPW = 2,080 Lumens)

www.ScottArchLighting.com | Tel (707) 864-2172 | Fax (707) 864-2182 © Copyright 2024 Scott Architectural Lighting. All Rights Reserved. Made in the USA.



