

S2425 Series

Indra 6




S2425 WITH CABLES



S2420 STEM



DIMENSIONS



W	X	H	BASE MODEL NO.
6"	11"	36"	S2420-L24 (Stem)
6"	11"	36"	S2425-L24 (Cables)

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided.

FEATURES

- Clear Silver Electrical Cord with (2) Adjustable Aircraft Cables or Single Stem
- Opal Matte Glass with Closed Bottom
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + CCT + Finish + Fabric + OA + Option Code

S2420-L24	+	27K	+	PT	+	OA	+	Option
S2425-L24		30K		BA				
		35K		BB				
		40K		BC				
				BN				
				PC				

FINISHES

BA Brushed Aluminum
 BB Brushed Brass
 BC Brushed Chrome
 BN Brushed Nickel
 PC Polished Chrome
 PT Powder Coated Finishes*
 *(Specify Color Code from the list of Powder Coating Finishes)

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.
 EML Remote 10W Emergency LED Battery Backup
 OA Specify Overall Height of Fixture in Inches; E.G. – OA48
 SWC 35-Degree Swivel Canopy
 OMA Opal Matte Acrylic with Closed Bottom

LIGHT OUTPUT

LXX = ~ 70 LPW Delivered Lumens (Example: L24= 24W x 70LPW = 1,680 Lumens)