




## DIMENSIONS



W	H	X	BASE MODEL NO.
13"	42"	28"	<b>S2520-L68</b>

## SPECIFICATIONS

**Driver:** 0-10V dimming to 1%, 120/277 [Excluding Downlight]

**Mounting:** Mounts to all Standard Electrical Junction Boxes (by others) with Hardware Provided

## FEATURES

- Opal Matte Acrylic
- 150 Watt PAR 38 Medium Base-Downlight Standard on Separate 120V Only Circuit
- Solid Bar Stock Material
- LED 0-10V Dimming Driver

## ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + Finish Code + OA + Option Code

S2520-L68 + 27K + PT + Option  
 30K BA  
 35K BB  
 40K BN

## FINISHES

**BA** Brushed Aluminum **BN** Brushed Nickel  
**BB** Brushed Brass **PT** Powder Coated Finishes\*  
 \*(Specify Color Code from the list of Powder Coating Finishes)

## OPTIONS

**BAC** Buy America; Buy American Act; and Build America, Buy America Act Compliant.  
**EML** Remote 10W Emergency LED Battery Backup  
**OA** Specify Overall Height of Fixture in Inches; E.G. – OA48  
**FAA** = Faux Alabaster Acrylic (Hand Painted) (FA1 White; FA2 Antique; FA3 Grey; FA4 Taupe; FA5 Honey; FA6 Tuscan)  
**SWC** 35-Degree Swivel Canopy  
**2C** = Two-Circuit Wiring

## LIGHT OUTPUT

**LXX** = ~ 69 LPW Delivered Lumens (Example: L68= 68W x 69LPW = 4,692 Lumens)