

S2630 Series


Cyla 12



SUPERCEDED BY S2B90 SERIES

This product is still available to complete existing specifications, quotes, bids and active orders. Please use the new part number for new applications and specifications.

DIMENSIONS



W	H	X	BASE MODEL NO.
12"	144"	48"	S2630-L48
12"	144"	72"	S2631-L72
12"	144"	96"	S2632-L96

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277 [Excluding Downlight]
Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided.

FEATURES

- Opal Matte Acrylic
- Clear Silver Braided Cord with (1) Adjustable Air Craft Cable
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + CCT + Finish + OA + Option Code
S2630-L48 + 27K + PT + OA + Option
S2631-L72 + 30K + BA
S2632-L96 + 35K + BB
+ 40K + BN

FINISHES

BA Brushed Aluminum **BN** Brushed Nickel
BB Brushed Brass **PT** Powder Coated Finishes*
 *(Specify Color Code from the list of Powder Coating Finishes)

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.
EML Remote 10W Emergency LED Battery Backup
OA Specify Overall Height of Fixture in Inches; E.G. – OA204
FAA Faux Alabaster Acrylic (Hand Painted) (FA1 White; FA2 Antique; FA3 Grey; FA4 Taupe; FA5 Honey; FA6 Tuscan)
SWC 35- Degree Swivel Canopy (Single Stem)
P38 Optional GU24 Socket for LED PAR38 Downlight 120 or 277V
1S Single Stem

LIGHT OUTPUT

LXX = ~ 83 LPW Delivered Lumens (Example: L48= 48W x 83LPW = 3,984 Lumens)