


# S2B40 Series

Cyla 3



## DIMENSIONS



W	H	X	BASE MODEL NO.
3"	96"	12"	S2B40-L12
3"	96"	24"	S2B41-L24
3"	96"	36"	S2B42-L36
3"	96"	48"	S2B43-L48
3"	120"	60"	S2B44-L60
3"	120"	72"	S2B45-L72

## SPECIFICATIONS

**Driver:** 0-10V dimming to 1%, 120/277 [Excluding Downlight]  
**Mounting:** Mounts to all Standard Electrical Junction Boxes (by others) with Hardware Provided

## FEATURES

- Opal Matte Acrylic Cylinder
- Clear Silver Braided Cord with (1) Adjustable Aircraft Cable
- LED 0-10V Dimming Driver

## ORDER AS A COMPLETE UNIT:

Model No.	+ Lamp Code	+ Finish	+ OA	+ Option Code
S2B40-L12	+ 27K	+ PT	TT	+ OA + Option
S2B41-L24	30K	BA	PWT	
S2B42-L36	35K	NT	BST	
S2B43-L48	40K	GT	CC	
S2B44-L60		ZT		
S2B45-L72		CT		

## FINISHES

BA Brushed Aluminum	TT Toffee Touch
NT Nickel Touch	PWT Pewter Touch
GT Gold Touch	BST Blackened Steel Touch
ZT Bronze Touch	CC Custom Painted Finish
CT Copper Touch	PT Powder Coated Finishes*

\*(Specify Color Code from the list of Powder Coating Finishes)

## OPTIONS

- BAC** Buy America; Buy American Act; and Build America, Buy America Act Compliant.  
**EML** Remote 10W Emergency LED Battery Backup  
**1S** Single Stem

## LIGHT OUTPUT

**LXX** = ~ 80 LPW Delivered Lumens (Example: L24= 24 x 80 = 1,920 Lumens)