S7080 Series










DIMENSIONS



 W
 H
 BASE MODEL NO.

 10"
 7 1/2"
 \$7080-L12

 14"
 11"
 \$7081-L12

 18"
 15"
 \$7082-L24

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided.

FEATURES

- Opal Glass Diffuser
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + L	₋amp Code	+ CCT	+ Finish	1 + Op	otion Co	ode
\$7080-L12 \$7081-L12 \$7082-L24	+	27K 30K 35K 40K	+	PT AP BA PB PC CC	+	Option

FINISHES

AP Aged Pewter
BA Brushed Aluminum
PB Polished Bras
*(Specify Color Code from the list of Powder Coating Finishes)

PC Polished Chrome
CC Custom Painted Finish
PT Powder Coated Finishes*

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.

EML Remote 10W Emergency LED Battery Backup (Requires Additional Power Cable)

LIGHT OUTPUT

LXX = ~ 75 LPW Delivered Lumens (Example: L12= 12W x 75LPW = 900 Lumens)





