


DIMENSIONS



W	H	D	MC	BASE MODEL NO.
8 1/8"	31"	4"	15 1/2"	S9350-L16
8 1/8"	43"	4"	21 1/2"	S9351-L24
8 1/8"	55"	4"	27 1/2"	S9352-L32

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided. Silicone Seal Required (by others).

FEATURES

- Opal Acrylic
- Solid Aluminum Material
- Solid Aluminum End Caps
- Solid Aluminum Accent Bars
- UL Listed for Wet Location
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + CCT + Finish + Option Code

S9350-L16	+	27K	+	PT	+	Option
S9351-L24		30K		BA		
S9352-L32		35K				
		40K				

FINISHES

BA Brushed Aluminum **PT** Powder Coated Finishes*

*(Specify Color Code from the list of Powder Coating Finishes [except interior only metallics])

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.

EML Remote 10W Emergency LED Battery Backup

LIGHT OUTPUT

LXX = ~ 75 LPW Delivered Lumens (Example: L16= 16W x 75LPW = 1,200 Lumens)

** Try our new **Shimmer Metallic Paints**, Formulated for Exterior Conditions.