


DIMENSIONS



W	H	D	MC	BASE MODEL NO.
8 1/2"	20"	4"	10"	S9360-L24
8 1/2"	24"	4"	12"	S9361-L16
8 1/2"	30"	4"	15"	S9362-L32
8 1/2"	37"	4"	18 1/2"	S9363-L34
8 1/2"	49"	4"	24 1/2"	S9364-L48

SPECIFICATIONS

Driver: 0-10V dimming to 1%, 120/277

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided. Silicone Seal Required (by others).

FEATURES

- Opal Acrylic
- Solid Aluminum End-Plates
- Solid Aluminum Bar Stock
- UL Listed for Wet Location
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + CCT + Finish + Option Code

S9360-L24	+	27K	+	PT	+	Option
S9361-L16		30K		BA		
S9362-L32		35K				
S9363-L34		40K				
S9364-L48						

FINISHES

BA Brushed Aluminum **PT** Powder Coated Finishes*

*(Specify Color Code from the list of Powder Coating Finishes [except interior only metallics])

OPTIONS

BAC Buy America; Buy American Act; and Build America, Buy America Act Compliant.

EML Remote 10W Emergency LED Battery Backup

HB Horizontal Bars

HB/PMD Horizontal Bars with Perforated Metal Diffuser

VB Vertical Bars

VB/PMD Vertical Bars with Perforated Metal Diffuse

LIGHT OUTPUT

LXX = ~ 77 LPW Delivered Lumens (Example: L24= 24W x 77LPW = 1,848 Lumens)

** Try our new **Shimmer Metallic Paints**, Formulated for Exterior Conditions.