S9470i Series










DIMENSIONS



DASE MODEL	IVIC	ט	П	VV
S9470i-L24	3 1/2"	6 7/8"	7"	13"
S9470i-L32	3 1/2"	6 7/8"	7"	13"
S9470i-L40	3 1/2"	6 7/8"	7"	13"

SPECIFICATIONS

Driver: 0-10V dimming, 120/277

Mounting: Mounts to all Standard Electrical Junction Boxes (by others) With Hardware Provided. Silicone Seal Required (by others).

FEATURES

۱۸/

- 3000/3500/4000K on-board optional CCT
- 24/32/40W on-board optional outputs
- IP65 Rating
- Type 3 Distribution Pattern
- Tempered Glass Lens
- Downlight Suitable for Wet Location
- Uplight Suitable for Damp Location
- UL Listed for Wet Location
- Full Cut-off Distribution
- LED 0-10V Dimming Driver

ORDER AS A COMPLETE UNIT:

Model No. + Lamp Code + CCT + Finish + Option Code										
\$9470i-L24 \$9470i-L32 \$9470i-L40	+	30K 35K 40K	+	PT GT CT ZT TT	NT PWT BST TA	+	Option			

FINISHES

GT Gold Touch **PWT** Pewter Touch **BST** Blackened Steel Touch **CT** Copper Touch **ZT** Bronze Touch TA Textured Anthracite CC Custom Painted Finish PT Powder Coated Finishes* TT Toffee Touch **NT** Nickel Touch

*(Specify Color Code from the list of Powder Coating Finishes [except interior only metallics]).

For specialty finishes consult factory.

IEML Integral Emergency 9W Driver PC Photocell

LIGHT OUTPUT

LXX = ~ 135 LPW Delivered Lumens (Example: L16 = 16W x 135LPW = 2,160 Lumens)


** Try our new **Shimmer Metalic Paints**, Formulated for Exterior Conditions.







SPECIAL FEATURES (these features come on all models)



3 Color Temperatures

On board switch allows for on-site adjustment to 3000/3500K/4000K options.

Note: For factory Pre-set, please indicate the CCT in the part number (ex: S9470-L24-**35K**-BL)

3 Power Levels

On Board Switch allows for on-site adjustment to 3 power levels.

40W/32W/24W

Note: For Factory Pre-Set Watts, please indicate the Watts in the part number (ex: S9470-L32-30K-BZ)



OFF ON

Photosensor

On Board Sensor and Switch allows an internal photocell to be turned on or off as needed.

NOTE: For Factory Pre-Set to ON, please indicate in the part number (ex: S9470i-L24-40K-BST-**PS**)

